



**R-2200AC-A**  
Air cap set with  
protective cover



**R-2200AC-B**  
Air cap set without  
protective cover

## Functions and Characteristics

- ◆ R-2200AC Air-assisted gun is a combination of traditional air spraying and airless spraying technology. It atomizes precisely to produce a stable coating spray surface. It can form a uniform coating surface on the workpiece with high transfer efficiency and fine spraying quality.
- ◆ R-2200AC is recommended for spraying: varnishes, lacquers, colours, solvented and water-based paint, high solid materials paint, is also suitable for one component and two component paint.

Model	R-2200AC
Air Cap	R24(Spray Width: Unadjustable)
Maximum Working Air Pressure	6 bar (87psi)
Usage Fluid Pressure	200 bar(20Mpa , 2900 psi )
Fluid Output	Depending On Tip Size
Maximum Operating Temperature	50 °C
Air Consum-ption	385 L/min(±10)
Transfer Efficiency	87 (±2 %)
Wetted Parts	Stainless Steel
Fluid Connector	1/4 NPS , Filter
Air Connector	1/4PF
Safety Device	Safety Lever ,Protection Cap
Material Filter	Fluid Connector the Inline filter (100mesh)
Noise Level	80 dBa (±2)
Spray Distance	200mm
Weight	620g (1.37 lbs)

R-2200AC Testing conditions: paint pressure=60; viscosity=20 s; air pressure=1.5 bar; temperature=20 °C; relative humidity=60%